


FOUNDATION PLAN NOTES:

- SURFACE FINISHED WITH CRUSHED STONE AND POLY V.B.
- FOUNDATION WALL 8" CONCRETE BLOCK WITH 2x 8 SILL PLATE BOLTED WITH ANCHOR BOLTS @ 48" O.C.
- FOOTING 18x 8 POURED CONCRETE WITH (2) #4 REBAR.
- CONCRETE SLABS 4" REINFORCED WITH 6x 6 10/10 W.W.F. ON 6 MIL. POLY AND 4" CRUSHED STONE.
- DOUBLE JOISTS UNDER PARALLEL PARTITIONS.
- BLOCKING OR BRIDGING WITH JOISTS WHERE NEEDED.

<p>Sheet</p> <p style="font-size: 24pt; font-weight: bold;">A.2</p> <p style="font-size: 10pt;">THE FOUNDATION PLAN</p> <p style="font-size: 8pt;">DATE: MARCH 5, 2004</p> <p style="font-size: 8pt;">REV</p> <p style="font-size: 8pt;">REV</p>	 <p style="font-weight: bold; font-size: 12pt;">PHOENIX RISING</p> <p style="font-size: 8pt;">ARCHITECTURAL DESIGN</p>	<p style="font-size: 8pt;">711 Lyndon Lane Louisville KY, 40222 362.425.9896 Fax: 362.425.9897</p>	<p style="font-weight: bold; font-size: 18pt;">KRISS LOWRY & ASSOCIATES</p> <p style="font-weight: bold; font-size: 12pt;">CORINTH, KY.</p> <p style="font-weight: bold; font-size: 10pt;">2BED-884-B</p>	<p>3004</p> <p style="font-size: 6pt;">All drawings and specifications are prepared by the architect and are subject to change without notice. The architect shall not be responsible for any errors or omissions in the drawings or specifications or for any consequences arising therefrom. The contractor shall be responsible for obtaining all necessary permits and for complying with all applicable laws, codes and regulations. The contractor shall also be responsible for protecting all existing structures and utilities on the site. The contractor shall not be allowed to make any changes to the drawings or specifications without the written consent of the architect.</p>
--	---	--	---	--